


How to measure your Ring Size

CONFIRM PRINTER SETTINGS



This guide is only accurate if printed properly, follow these instructions to set up your printer correctly.

1. Print only on A4 paper, and access printing settings by pressing CTRL + P (Command + P on Mac) and making sure that your page scaling is set to 100%, DO NOT print with fit to screen option, it will not print accurately.
2. Take a ruler and measure the left bar, it must be exactly 3 cm.



HOW TO MEASURE CURRENT RING SIZE

1. Find the ring you want to measure and place it on one of the circles below.
2. Match the dotted circle to the inside of the ring, making it fit perfectly in line.
3. Ensure that the dotted line matches the inside of the ring, there should be no gap between the dotted line and the inside of the ring at any point.



D. 0.554in
C. 1.74in



D. 0.57in
C. 1.79in



D. 0.586in
C. 1.84in



D. 0.602in
C. 1.89in



D. 0.618in
C. 1.94in



D. 0.634in
C. 1.99in



D. 0.65in
C. 2.04in



D. 0.666in
C. 2.09in



D. 0.682in
C. 2.14in



D. 0.698in
C. 2.19in



D. 0.714in
C. 2.24in



D. 0.73in
C. 2.29in



D. 0.746in
C. 2.34in



D. 0.762in
C. 2.39in



D. 0.78in
C. 2.44in



D. 0.794in
C. 2.49in



D. 0.81in
C. 2.54in



D. 0.826in
C. 2.59in



D. 0.842in
C. 2.64in



D. 0.858in
C. 2.69in



D. 0.882in
C. 2.76in



D. 0.898in
C. 2.82in



D. 0.906in
C. 2.84in

DIAMONDS[™] FACTORY

International Ring Size Chart

BRITISH IRISH AUSTRALIAN SIZE	US CANADA SIZE	INSIDER DIAMETER (INCHES)	INSIDER DIAMETER (MM)	INSIDER CIRCUMFERENCE (INCHES)	INSIDER CIRCUMFERENCE (MM)
F 1/2	3	0.554	14.1	1.74	44.2
G	3.25	0.562	14.3	1.765	44.8
G 1/2	3.5	0.57	14.5	1.79	45.5
H	3.75	0.578	14.7	1.815	46.1
H 1/2	4	0.586	14.9	1.84	46.7
I	4.25	0.594	15.1	1.865	47.4
I 1/2	4.5	0.602	15.3	1.89	48
J	4.75	0.61	15.5	1.915	48.7
J 1/2	5	0.618	15.7	1.941	49.3
K	5.25	0.626	15.9	1.966	49.9
K 1/2	5.5	0.634	16.1	1.991	50.6
L	5.75	0.642	16.3	2.016	51.2
L 1/2	6	0.65	16.5	2.041	51.8
M	6.25	0.658	16.7	2.066	52.5
M 1/2	6.5	0.666	16.9	2.091	53.1
N	6.75	0.674	17.1	2.116	53.8
N 1/2	7	0.682	17.3	2.141	54.4
O	7.25	0.69	17.5	2.167	55
O 1/2	7.5	0.698	17.7	2.192	55.7
P	7.75	0.706	17.9	2.217	56.3
P 1/2	8	0.714	18.1	2.242	56.9
Q	8.25	0.722	18.3	2.267	57.6
Q 1/2	8.5	0.73	18.5	2.292	58.2
R	8.75	0.738	18.7	2.317	58.9
R 1/2	9	0.746	18.9	2.342	59.5
S	9.25	0.754	19.2	2.368	60.1
S 1/2	9.5	0.762	19.4	2.393	60.8
T	9.75	0.77	19.6	2.418	61.4
T 1/2	10	0.781	19.8	2.443	62.1
U	10.25	0.788	20	2.468	62.7
U 1/2	10.5	0.794	20.2	2.493	63.3
V	10.75	0.802	20.4	2.518	64
V 1/2	11	0.81	20.6	2.543	64.6
W	11.25	0.818	20.8	2.569	65.2
W 1/2	11.5	0.826	21	2.594	65.9
X	11.75	0.834	21.2	2.619	66.5
X 1/2	12	0.842	21.4	2.644	67.2
Y	12.25	0.85	21.6	2.669	67.8
Y 1/2	12.5	0.858	21.8	2.694	68.4
Z	12.75	0.866	22	2.719	69.1
Z+1	13.25	0.882	22.4	2.769	70.3
Z+3	3.75	0.898	22.8	2.82	71.6
Z+4	14	0.906	23	2.845	72.3